# Ohme Home Pro

## Introducing the Ohme Home Pro, your EV's new best friend.

Our latest home EV charger, featuring an interactive LCD screen, displays live charge data and gives you the option to control your charging from the charger itself.

- Integrates with your energy tariff to charge at the cheapest and greenest times
- Control your charging via the interactive LCD screen or our trusted app
- Quick, compact and discreet installation
- Keep control of your costs with our max price cap setting
- Track your CO2 consumption with our 'Green Score' feature
- Feel confident that your car will be ready to go when you are

"100% I'd recommend Ohme all the way, above every other product. There is level of flexibility with Ohme that you don't get with other providers."

- Kaushik B

#### Protect your purse and our planet.

Ohme offers a home charging solution that protects your car, your purse, and our planet.

Ohme could save drivers in Ireland up to €275-350\* a year compared to a standard charger and tariff.

\*Savings based on an annual mileage of 12,000 miles with EV specific smart tariff.

Penrose Wharf, Penrose Quay, Cork, T23 HF51, Ireland +353 21 601 0311




Shme

#### **Features and Benefits**

#### **Charger Specifications**

- Interactive LCD screen
- Schedule charging, input a target battery % and add a price cap per kWh via the charger or Ohme app
- Tethered cable ease of connection to EV
- Energy tariff and vehicle integration
- Over-the-air firmware/ software upgrades



D: 100mm H------H Freedow 1:42 Grand Market Constants 56% www. Base Base Market Constants Compage 3:100 Market Constants C

Chme





### Electrical

- In-built protective earth neutral (PEN) fault device
- Dynamic load balancing
- LCD screen
- Power output/Max current: 7.4kW/32A
- Nominal supply: 230 V AC, 50/60 HZ
- Protection: RCD Type A with 6 mA DC
- Overcurrent protection: not fitted, to be fitted separately.

#### Mechanical

- Dimensions (H/W/D): 170mm / 200mm
  /100mm
- Weight: 5m = 5.3kg, 8m = 6.5kg
- Output cable length: 5 or 8 metres
- Flying lead cable length: 1 metre
- Ingress protection degree: IP55
- Operation temp: -25 degrees to 45 degrees
- Storage temp: -40 degrees to 85 degrees

#### **Function**

• 2G/3G/4G multinet sim card - cost covered by Ohme for the first 3 years

#### Compliance

- SEAI approved
- UKCA marked



